

SYMBOL	TYPE	PRODUCT NAME	CONTACT NAME / NUMBER
		FLUORESCENT (Insect Proof)	



HOUSING		WIRING CABLE				
<p>HIGH GRADE DIE-FORM STEEL SHEET.</p> <p>SIX-STAGES ZINC-PHOSPHATE PRE-TREATMENT FOR RUST RESISTANT , FINISHED WITH WHITE POLTESTER POWDER BY ELECTROSTATIC METHOD TWO STAGES AND BAKED ENAMEL .</p> <p>THICKNESS <input type="checkbox"/> 0.6 mm , <input type="checkbox"/> 0.8 mm</p>		<p>THW 1x1.0 SQ.MM. 70 °C</p> <p>WIRING CABLE (STANDARD)</p>				
DIFFUSER		LOUVER				
<p>OPAL GLASS WITH LOCKING RING SYSTEM AND EXCELLENT WEATHERPROOF RUBBER GASKET, PREVENT ANY INSECTS TO ACCUMULATE IN LUMINAIRE (PATENT B.E. 2522)</p>		<p>NONE</p>				
REFLECTOR		LAMP AND HOLDER				
<p>NONE</p>		<p>E27 TYPE LAMP HOLDER</p>				
STANDARD		INSTALLATION				
<p>TIS.902 ๓๕๓2 (1) - 2557 WITH CLASS I AND F MARK</p> <p>TIS.1955-2551</p>		<p>SURFACE MOUNTED</p>				
MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
DLCL-1101 (E27)		E27	432	432	80	