Saensmitr


ISO 9001 : 2015


Products Data Sheet



SYMBOL TYPE PRODUCT NAME CONTACT NAME / NUMBER

LED LINEAR LIGHT





SPECIFICATIONS		DESCRIPTION	
INPUT VOLTAGE	: 220VAC, 50Hz	DIE-CASTING END-CAPS. NO SCREW TO BE APPEARED,	
LED POWER	: 2×10W+20W	NO LIGHT LEAK.	
LED CHIP	: LED SMD 2835	HIGH GRADE ALUMINUM, HIGH QUALITY	
LUMEN FLUX	: 3,600lm	SURFACE PAINTING.	
LUMINOUS EFFICACY	: 90lm/W	FAST AND EASY CONNECTION WITH NO SHADOW.	
COLOR RENDERING INDEX	: Ra80		
COLOR TEMPERATURE	: 3000K/4000K/5000K/5700K		
LED LIFETIME	: 50,000 HOURS	INSTALLATION	
		SURFACE CEILING MOUNTED	
		STANDARD	
		TIS. 1955-2551	

MODEL -	LAMP		DIMENSION (mm.)		n.)	REMARK
	WATT	TYPE	L	w	Н	REWARK
DLED-802M2-1800	×10W+20V	LED	1690	65	90	